



Xerox[®] VersaLink[®] C620 Color Printer is built on Xerox[®] ConnectKey[®] Technology. For more information, go to **ConnectKey.com**.

System Specification				
Speed ¹	Color and Black-and-White: Up to 52/50 ppm Letter/A4			
	Duplex Print Speed: 40/38 ipm Letter/A4			
Monthly Duty Cycle ²	Up to 150,000 pages			
Recommended Average Monthly Print Volume	Up to 20,000 pages			
Processor/Memory/ Hard Drive	Quad Core 1.2GHz/2 GB system memory/32GB eMMC/ Optional: 500+GB HDD			
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 2.0 direct print, NFC; Optional: Wi-Fi®/Wi-Fi Direct® with Xerox® Dual Band WiFi® and Bluetooth® Kit (Bluetooth for iBeacon™)			
Controller Features	Unified Address Book, Remote Control Panel, Configuration Cloning, Fleet Orchestrator, Configuration Watchdog, Security Dashboard			
Print				
Print Resolution	Print: Up to 1200 x 1200 dpi			
First-Print-Out Time (as fast as)	6.6 seconds color/5.6 seconds black-and-white			
Page Description Language	Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6			
Print Features	Print from USB, Print from Cloud Repositories (Dropbox, OneDrive, and Google Drive), Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Booklet Layout, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs, Print Around, Print on Alternate Paper			
Mobile and Cloud Ready				
Universal Print Ready	Microsoft Universal Print is a cloud print service, available to Microsoft 365 subscribers. It removes the need for on-site print servers and leverages the built-in drivers included in the Windows 10 and 11 PCs. You can enjoy the benefits of cloud hosting with a driverless setup for all Windows 10 and 11 clients. Utilize the Print Support App (PSA) by Xerox (Requires installation of Xerox Print and Scan Experience) to gain access to the Xerox Print Properties user interface			
Mobile Connectivity	Near Field Communication (NFC); Optional: Wi-Fi Direct, Wi-Fi (802.11 b/g/n/ac)AirPrint (iOS) including iBeacon ³ (Bluetooth) for AirPrint Discovery			
Mobile Printing	Mopria® Print, Apple® AirPrint®, Xerox® Print Service (Android), Xerox®@PrintByXerox App; Optional: Xerox® Workplace App (iOS/Android), iBeacon ³ (Bluetooth) for AirPrint Discovery			
Mobile Apps and Xerox App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalize, print, convert, route, collaborate, and communicate. Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services: Xerox® DocuShare® Content Management Platform (xerox.com/ecm), XMPie® (xerox.com/XMPie), Xerox® Workplace Solutions (xerox.com/WorkplaceSolutions)			

Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox [®] Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution		
Cloud Identity Provider (IdP) Integration	Use your desktop, laptop, or mobile login credentials to log in to your VersaLink® MFPs with direct connections to popular cloud identity providers Okta, Ping Identity, and Microsoft® Azure		
Security			
Standard Features	Access Control, AES 256-bit, Audit Log, Automatic Self-signed Certificate, Automated threat response through Trellix DXL [#] , Cisco [®] Identity Services Engine (ISE) Integration, Common Criteria Certification, Configuration Watchdog, Encrypted Secure Print, FIPS 140-3, Firmware Verification, HTTPS, Immediate Image Overwrite ⁴ for optional hard disks, IPsec, Job Level Encryption via HTTPS and Drivers, Local Authentication (Internal Database), LogRhythm SIEM integration, Microsoft Universal Print/IPP with Print Support Application (Secure Print and Secure Release), Network Authentication, Port/IP/Domain Filtering, Security Certificates utilizing ECDSA, Security Manager, Security Templates, Serverless Card Authentication, SFTP and Encrypted Email, SIEM integration (Splunk, LogRhythm, Trellix ESM*), Signed Email, SNMPv3, SHA-256 Hash Message Authentication, TLS1.1/1.2/1.3, Trellix Embedded Control Whitelisting/Allowlisting [#] , Trellix ePolicy Orchestrator ^{®#} , Trusted Boot, Trusted Platform Module (TPM 2.0), User Access, User Permissions, 802.1x		
Optional Features	Xerox® RFID Card Reader Kits, 500+GB Hard Disk, AES 256-bit, FIPS 140-3, with multi-pass Image Overwrite ⁴ , Xerox® Workplace Cloud/Suite Print Management and Content Security, WPA2™ and WPA3™ with Xerox® Dual Band WiFi® and Bluetooth® Kit (Bluetooth for iBeacon™), Xerox Workplace Cloud/Suite Print Management and Content Security, learn more at xerox.com/WorkplaceSolutions		
Print Management			
Standard Features	Xerox® Standard Accounting Feature (Print, Email), Network Accounting Enablement		
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print Management Services; learn more at xerox.com/PrintManagement		
Print Management Standard Features	LogRhythm, Trellix ESM*), Signed Email, SNMPv3, SHA-256 Hash Message Authentication, TLS1.1/1.2/1.3, Trellix Embedded Control Whitelisting/Allowlisting [#] , Trellix ePolicy Orchestrator ^{®#} , Trusted Boot, Trusted Platform Module (TPM 2.0), User Access, User Permissions, 802.1x Xerox® RFID Card Reader Kits, 500+GB Hard Disk, AES 256-bit, FIPS 140-3, with multi-pass Image Overwrite ⁴ , Xerox® Workplace Cloud/Suite Print Management and Content Security, WPA2 [™] and WPA3 [™] with Xerox® Dual Band WiFi [®] and Bluetooth [®] Kit (Bluetooth for iBeacon [™]), Xerox Workplace Cloud/Suite Print Management and Content Security, learn more at xerox.com/WorkplaceSolutions Xerox® Standard Accounting Feature (Print, Email), Network Accounting Enablement Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox [®] Business Innovation Partners.		

Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

xerox

1

Features and Accessories

				-		1
	<u>.</u>		& Log In	Home		
=			Print From		O- O- Device	
			Connect for XMPve	Xerce® App Gallery		
			-	-		
		The ir	ituitive, to	ablet-like	5.in	chi
		1 Inc II	ituitive, ti	inter-like	., J-m	cii

The intuitive, tablet-like, 5-inch touch screen allows you to personalize your experience to get more done in fewer taps. Gain access to an array of productivity boosting apps through the Xerox App Gallery.

ې چې

The 550-Sheet Tray handles media sizes from 4.1 x 5.8 in to 8.5 x 14 in/105 x 148 mm to 216 x 356 mm (Includes 550-sheets standard capacity and additional 100-sheet bypass tray)

The 100-Sheet Bypass Tray handles media sizes from 3 x 5 in to 8.5 x 14 in/76.2 x 127 mm to 216 x 356 mm

OPTIONAL PAPER FEEDING

550-Sheet Tray

Add up to 4 additional 550-sheet trays for a total paper capacity of 2,850 sheets

2

OPTIONAL ACCESSORIES

Card Reader Kit

500+GB Hard Disk

Printer Stand

Add to busy devices to enhance performance and increase capacity for storage, collation and image processing of large-size jobs, 1-Touch Apps, customer-installable fonts, and enable copy build job.





Adjustable Stand

XEROX[®] EASY ASSIST APP

Xerox Easy Assist App provides easy set up and allows you to securely manage your device on the go right from your mobile phone, with real-time monitoring of printer performance and instant access to self-support services - all without the need for any IT support. Learn more at **xerox.com/EasyAssist**.





Wi-Fi Direct.

Wireless Network Adapter

Enables wireless connectivity

and includes support for

Device Specification			
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic, Croatian, Ukrainian		
Accessories			
Optional	Wireless Network Adapter 500+GB HDD Unicode Font Kit ⁹ Trellix Integrity Control Enablement Kit [#]		
Electrical Requirements			
North America	Voltage: 110–127 VAC +/-10% Frequency: 50/60Hz +/- 3%, 10A		
Europe	Voltage: 220–240 VAC +/-10% Frequency: 50/60Hz +/- 3%, 5A		
Power Consumption			
Running (Average)	Simplex 702W Duplex 581W		
Standby Mode	25W		
Auto Off/Sleep Mode	1.0W		
Warm-up (from Off)	116 sec		
Recovery from Sleep	As fast as 2.9 seconds		
Typical Energy Consumption	0.65kwh		
Operating Environment			
Required Temperature Range	50 to 90°F/10 to 32.2°C		
Required Relative Humidity	15 to 80% RH		
Sound Power Levels	Operating: 7 B(A) or less Standby: 3 B(A) or less		
Sound Pressure Levels	Operating: 55 db(A) or less Standby: 14 db(A) or less		
Dimensions and Weight	Packaged	Unpackaged	
Base Configuration	Width: 24.6 in/625 mm Depth: 28.4 in/720 mm Height: 22.3 in/567 mm Weight: 85 lbs/38.5 kg	Width: 18.9 in/479 mm Depth: 19.2 in/489 mm Height: 16.2 in/413 mm Weight: 71 lb/32 kg	
550-Sheet Tray	Width: 20.7 in/527 mm Depth: 22 in/558 mm Height: 8.5 in/216 mm Weight: 19.7 lb/8.9 kg	Width: 18.2 in/463 mm Depth: 19 in/483 mm Height: 4.7 in/119 mm Weight: 15 lb/6.8 kg	
Printer Stand	Width: 20.7 in/525 mm Depth: 22.2 in/565 mm Height: 9.2 in/235 mm Weight: 37.7 lb/17.1 kg	Width: 18.2 in/463 mm Depth: 20 in/510 mm Height: 17.3 in/440 mm Weight: 32.7 lb/14.8 kg	
Adjustable Stand	Width: 27.2 in/690 mm Depth: 26.3 in/670 mm Height 9.1 in/232 mm Weight: 62.6 lb/28.4 Kg	Width: 24.6 in/626 mm Depth: 23.5 in/597 mm Height: 20.5 in/521 mm Weight: 50.9 lb/23.1 Kg	
System Certifications/Regul	atory Compliance		
Certifications	To view the latest list of certifications, go to xerox.com/OfficeCertification	ns	

Paper Handling			
Bypass Tray (Standard)			
Capacity ⁵	100 sheets		
Sizes	Custom Sizes: 3 x 5 in to 8.5 x 14 in/76.2 x 127 mm to 216 x 356 mm		
Weights	16 to 58 lb bond/60 to 218 gsm		
Media Types	Bond Card Stock Custom Envelopes Glossy Card Stock ¹⁰ Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted Recycled		
Trays 1 (Standard)			
Capacity⁵	550 sheets		
Sizes	Tray 1: Custom Sizes: 4.1 x 5.8 in to 8.5 x 14 in/105 x 148 mm to 216 x 356 mm		
Weights	16 to 58 lb bond/60 to 218 gsm		
Media Types	Bond Card Stock Custom Envelopes Glossy Card Stock ¹⁰ Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted Recycled		
Optional Paper Feeding			
Capacity⁵	550-Sheet Tray: Add up to 4 additional 550-sheet trays		
Sizes	4.1 x 5.8 in to 8.5 x 14 in/105 x 148 mm to 216 x 356 mm		
Weights	16 to 58 lb bond/60 to 218 gsm		
Media Types	Bond Card Stock Custom Envelopes Glossy Card Stock ¹⁰ Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted Recycled		
Total Capacity			
Device Total Capacity ⁵	Base Model: 650 sheets 550-Sheet Tray: Add up to 4 additional 550-sheet trays for a total capacity of 2,850 sheets Paper Output: 300 sheets		

Print	
Resolution (up to)	1200 x 1200 dpi
Print Features	Application Defaults Banner Sheet Enable/Disable Booklet Layout Cover Selection Fit to New Paper Size Hold All Jobs Image Options (Resolution (Enhanced, High) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Layout/Watermark N-up (up to 16 pages per sheet) Paper Selection by Attribute Print From Cloud Repositories (Dropbox, OneDrive, and Google Drive) Sample Set Saved Job (color jobs can be printed as black-and-white) Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox [®] Earth Smart, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) Two-sided Printing (as default) User Permissions
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, PCL Color jobs can be printed as black-and-white
Operating Systems	Windows Server 2016 Windows Server 2019 Windows Server 2022 Windows 10 Windows 11 Mac OS 12.x, 13.x, 14.x Fedora® Core Ubuntu® iOS Android For latest supported versions please visit our Drivers & Downloads page and specify your device at support.xerox.com
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD Microsoft Windows Networking over IP Support for Microsoft Universal Print Bonjour® AirPrint® Mopria® IPv6 Most protocols not in use can be disabled
Font Capability	PCL: 93 scalable fonts, line printer, and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade, and manage Xerox® Devices and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management.
Xerox [®] Pull Print Driver	Makes it easy for IT managers to qualify, deploy, and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.

Security	
Features	• Audit Log
	Cisco® Identity Services Engine (ISE) compatible
	Configuration Watchdog (Monitors and remediates security settings in the following areas):
	– 802.1x
	– Admin Password Reset
	– Audit Log
	– Automatic Software Upgrade
	– Email Alerts
	– FIPS 140
	- Hold All Jobs
	– Immediate Job Overwrite ⁴
	– Installation Policies
	– PII - Login Name
	– PostScript Passwords
	 Remote Services Enablement
	– Remote Start (TWAIN)
	 Reprint Saved Jobs
	 Scheduled Disk Overwrite⁴
	Secure Print Device Policies
	– SIEM
	– SNMP
	– System Timeout
	– USB (Print from USB)
	– USB Port Management
	– User Data Encryption
	Expanded Authentication
	– Digitally signed PDF (when using Smart Card authentication)
	 Encrypted/Password Protected PDF (when using Email Templates only)
	 FIPS 140 256 bit Hard Disk Encryption⁴, TLS 1.1/1.2/1.3, IPPS, HTTPS, SFTP, SNMPv3
	 Immediate Image Overwrite/Securely delete jobs using approved algorithms⁴
	– Local Authentication (internal database)
	 Network authentication to access device and/or device services via Kerberos (UNIX/Windows Server 2008), SMB (Windows Server 2008,
	Windows server 2012), NDS, LDAP authentication
	 On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk⁴
	 Smart Card authentication – 144k CAC/PIV Card Support (2048 bit certificate key)/.NET
	– Secure Data
	 Secure Print (up to 10 digit PIN or Network Authentication)
	Expanded Authorization
	Authorization per user per service
	 SA access based on network credentials
	– Secure Network Access
	 User Permissions required to access Print and Print Features (e.g., color access, or time restrictions) reflects in the print driver
	Hide Print Job Names
	 IP Filter, IPsec, IPv6, TLS V1.0, V1.2, V1.3, SNMP V1/V2/V3, HTTPs, 802.1X, SFTP
	Port disablement including USB ports
	Splunk SIEM integration
	Secure Print (up to 10 digit PIN or Network Authentication)
	Security Dashboard
	 Security Information and Event Management (SIEM) support for Trellix Enterprise Security Manager[#], LogRhythm, and Splunk
	Security Templates
	 Trellix Embedded Control[#] (whitelisting/allowlisting), Trellix Integrity Control[#] (optional)
	Trusted Platform Module 2.0
	WPA2 [™] and WPA3 [™] are supported by the Dual Band Wi-Fi [®] and Bluetooth [®] Kit

Device Management	
Administrative Protocols	DHCP, BOOTP, SNMP, SLP [®] v2, HTTP, HTTPS, AutoIP (Self Assigned Address)/DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS, Bonjour
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System-Power MIB, Fleet Orchestrator, Configuration Watchdog, Security Dashboard, Xerox Easy Assist App
Xerox [®] Easy Assist App	Xerox Easy Assist App provides easy set up and allows you to securely manage your device on the go right from your mobile phone, with real-time monitoring of printer performance and instant access to self-support services — all without the need for any IT support.
Xerox® CentreWare® Web Software	 A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running on Windows, UNIX, or any other operating system: Works with any SNMP-managed printer from any manufacturer Remote configuration of SNMP v3 Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management Auto-detect Xerox[®] CentreWare[®] Web Software server and download configurations files for touchless remote install
Xerox® Device Manager	 Optional: Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor, and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: Device monitoring and troubleshooting Remote configuration of SNMP v3 Extensive reporting and discovery of new devices Usage collection, chargeback, and billing capabilities Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install
Xerox [®] Workplace Cloud	Optional: Remote management to set and audit device configuration data with Xerox [®] Workplace Cloud, eliminating the need for an on-site server
Accessibility	 Embedded Web Server conforms to Web Content Guidelines (WCAG) Touchscreen zoom and pan Touchscreen navigation with keyboard Speech output
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files, and 1-Touch App files. Auto-assembly feature allows a new VersaLink® to automatically set itself up on the network to be automatically configured
Xerox [®] Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download. office.xerox.com/Software-Solutions
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at office.xerox.com/Software-Solutions
	1. A second s
Xerox [®] Embedded Web Serve	er – Integrated Device Web Pages Provided by the Device
Xerox® Embedded Web Serve Device Status	er – Integrated Device Web Pages Provided by the Device Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts • Remote Control Panel
	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts
Device Status	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel Print-ready files: PS, PCL, TIFF, PDF, JPEG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure,
Device Status Job Submission Device Administration Browsers	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel Print-ready files: PS, PCL, TIFF, PDF, JPEG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint) Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard, Security Template Brave Browser Chrome Microsoft Edge Mozilla Firefox Opera Safari
Device Status Job Submission Device Administration Browsers Support	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel Print-ready files: PS, PCL, TIFF, PDF, JPEG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint) Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard, Security Template Brave Browser Chrome Microsoft Edge Mozilla Firefox Opera Safari Install print drivers and online support available via support.xerox.com
Device Status Job Submission Device Administration Browsers	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel Print-ready files: PS, PCL, TIFF, PDF, JPEG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint) Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard, Security Template Brave Browser Chrome Microsoft Edge Mozilla Firefox Opera Safari
Device Status Job Submission Device Administration Browsers Support	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel Print-ready files: PS, PCL, TIFF, PDF, JPEG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint) Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard, Security Template Brave Browser Chrome Microsoft Edge Mozilla Firefox Opera Safari Install print drivers and online support available via support.xerox.com International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish,
Device Status Job Submission Device Administration Browsers Support Languages Supported	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel Print-ready files: PS, PCL, TIFF, PDF, JPEG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint) Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard, Security Template Brave Browser Chrome Microsoft Edge Mozilla Firefox Opera Safari Install print drivers and online support available via support.xerox.com International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish,
Device Status Job Submission Device Administration Browsers Support Languages Supported Remote Services Automatic Meter	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel Print-ready files: PS, PCL, TIFF, PDF, JPEG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint) Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard, Security Template Brave Browser Chrome Microsoft Edge Mozilla Firefox Opera Safari Install print drivers and online support available via support.xerox.com International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic, Croatian, Ukrainian
Device Status Job Submission Device Administration Browsers Support Languages Supported Remote Services Automatic Meter Readings (AMR) Automatic Supplies	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel Print-ready files: PS, PCL, TIFF, PDF, JPEG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint) Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard, Security Template Brave Browser Chrome Microsoft Edge Mozilla Firefox Opera Safari Install print drivers and online support available via support.xerox.com International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic, Croatian, Ukrainian Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time
Device Status Job Submission Device Administration Browsers Support Languages Supported Remote Services Automatic Meter Readings (AMR) Automatic Supplies Replenishment (ASR) Workplace Cloud Direct Accounting	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel Print-ready files: P5, PCL, TIFF, PDF, JPEG, TXT, PRN Output fedure selection (2-sided, output color, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint) Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard, Security Template Browe Browser Chrome Microsoft Edge Mozilla Firefox Opera Safari Install print drivers and online support available via support.xerox.com International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic, Croatian, Ukrainian Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time Automatically orders supplies for Xerox® Devices based on actual usage, eliminating the need to manually manage supplies inventory Embedded device agent technology allows your printer to connect directly with Xerox Workplace Cloud for a zero network footprint offering a 'true' cloud-only Print Management and Mobile s
Device Status Job Submission Device Administration Browsers Support Languages Supported Remote Services Automatic Meter Readings (AMR) Automatic Supplies Replenishment (ASR) Workplace Cloud Direct Accounting Xerox® Standard Accounting	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts • Remote Control Panel Print-ready files: PS, PCL, TIFF, PDF, JPEG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint) Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard, Security Template Brave Browser Chrome Microsoft Edge Mozilla Firefox Opera Safari Install print drivers and online support available via support.xerox.com International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic, Croatian, Ukrainian Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time Automatically orders supplies for Xerox® Devices based on actual usage, eliminating the need to manually manage supplies inventory Embedded device agent technology ollows your printer to connect directly with Xerox Workplace Cloud for a zero network footprint offering a 'true' cloud-only Print Management and
Device Status Job Submission Device Administration Browsers Support Languages Supported Remote Services Automatic Meter Readings (AMR) Automatic Supplies Replenishment (ASR) Workplace Cloud Direct Accounting	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel Print-ready files: P5, PCL, TIFF, PDF, JPEG, TXT, PRN Output fedure selection (2-sided, output color, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint) Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard, Security Template Browe Browser Chrome Microsoft Edge Mozilla Firefox Opera Safari Install print drivers and online support available via support.xerox.com International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic, Croatian, Ukrainian Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time Automatically orders supplies for Xerox® Devices based on actual usage, eliminating the need to manually manage supplies inventory Embedded device agent technology allows your printer to connect directly with Xerox Workplace Cloud for a zero network footprint offering a 'true' cloud-only Print Management and Mobile s
Device Status Job Submission Device Administration Browsers Support Languages Supported Remote Services Automatic Meter Readings (AMR) Automatic Supplies Replenishment (ASR) Workplace Cloud Direct Accounting Xerox® Standard Accounting Tracking	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts • Remote Control Panel Print-ready files: PS, PCL, TIFF, PDF, JPEG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint) Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard, Security Template Brave Browser Chrome Microsoft Edge Mollar Firefox Opera Safari Install print drivers and online support available via support.xerox.com International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic, Croatian, Ukrainian Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time Automatically orders supplies for Xerox® Devices based on actual usage, eliminating the need to manually manage supplies inventory Embedded device agent technology allows your printer to connect directly with Xerox Workplace Cloud for a zero network footprint offering a 'true' cloud-only Print Management and

Accounting (continued)					
Accounting Options – Network Accounting (Allows central server to manage all accounting)					
	Counting Options – Network Accounting (Allows central server to manage all accounting) Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage of print Numerous solutions are available through Xerox Alliance Partners. For details, visit xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third-party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third-party Networking Account Interface with third-party accounting terminal for accounting user interface				
Installation Considerations					
Clear area around the device is necessary for access and ventilation.	vice is necessary for Rear: 4 in/102 mm				
What's In The Box					
All items contained in VersaLink® C620 Color Printer the box: AC Power Cord Installation Guide Installation Flyer Product Information Flyer Product Safety Sheet Software Update Flyer Software and Documentation CD CMY Print Cartridges: 7,000 page capacity ⁶ K Print Cartridge: 8,000 page capacity ⁶					
Xerox [®] Supplies and Accesso	pries	North America and Europe*	All other regions		
Genuine Xerox Black Stand	ard Capacity Toner Cartridge, Xerox® VersaLink® C620 Color Printer (8,000 Pages) ⁶	006R04616	006R04620		
Genuine Xerox Cyan Stando	ard Capacity Toner Cartridge, Xerox® VersaLink® C620 Color Printer (6,000 Pages)6	006R04617	006R04621		
Genuine Xerox Magenta St	andard Capacity Toner Cartridge, Xerox® VersaLink® C620 Color Printer (6,000 Pages) ⁶	006R04618	006R04622		
Genuine Xerox Yellow Stand	dard Capacity Toner Cartridge, Xerox® VersaLink® C620 Color Printer (6,000 Pages) ⁶	006R04619	006R04623		
Genuine Xerox Black High C	Capacity Toner Cartridge, Xerox® VersaLink® C620 Color Printer (20,000 Pages) ⁶	006R04624	006R04632		
Genuine Xerox Cyan High C	apacity Toner Cartridge, Xerox® VersaLink® C620 Color Printer (12,000 Pages) ⁶	006R04625	006R04633		
Genuine Xerox Magenta Hi	gh Capacity Toner Cartridge, Xerox® VersaLink® C620 Color Printer (12,000 Pages) ⁶	006R04626	006R04634		
Genuine Xerox Yellow High	Capacity Toner Cartridge, Xerox® VersaLink® C620 Color Printer (12,000 Pages) ⁶	006R04627	006R04635		
Genuine Xerox Waste Toner	Bottle, Xerox [®] VersaLink [®] C620 Color Printer (170,000 Pages) ⁷	008R13334	008R13334		
Genuine Xerox Black Imagi	ng Kit, Xerox® VersaLink® C620 Color Printer (150,000 Pages) ⁸	013R00697	013R00697		
Genuine Xerox 3 Color Ima	ging Kit, Xerox® VersaLink® C620 Color Printer (150,000 Pages) ⁸	013R00698	013R00698		
Optional Accessories					
550-Sheet Tray		097N02441			
500+GB Hard Disk		097N02443			
Wireless Network Adapter		097N02470			
Printer Stand		097S05244			
Adjustable Stand		497N07994			
North America (NA): U.S. Canada ¹ Declared in accordance with ISO/IEC 24734					

* North America (NA): U.S., Canada

Europe (XE): U.K., France, Germany, Spain, Italy, Netherlands, Belgium, Norway, Sweden, Finland, Denmark, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland Andorra, Azores, Corsica, Greenland, Iceland, Lichtenstein, Luxembourg, Madeira, San Marino. " Trellix DXL formerly known as McAfee® DXL, Trellix Embedded Control Whitelisting formerly known

as McAfee® Embedded Control Whitelisting, Trelix ePolicy Orchestrator® formerly known as McAfee® ePolicy Orchestrator®, Trellix ESM formerly known as McAfee® ESM, Trellix Integrity Control Enablement Kit formerly known as McAfee® Integrity Control Enablement Kit, Trellix Enterprise Security Manager formerly known as McAfee® Enterprise Security Manager. Trellix brand name will be reflected in future firmware releases.

¹ Declared in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis. Wireless Network Adapter is required for iBeacon. Requires 500+GB Hard Disk.

Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

⁶ Average standard pages. Declared in accordance with ISO/IEC 19798. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes, and image quality set-points.

Waste Toner Container yield will vary depending on type of image, area coverage %, and Job run length. ⁸ Average drum yield is based on a run length of 5 pages of 8.5 x 11 in/A4 LEF pages, with split of 35 % color/65% black-and-white pages.

xerox

Not available in all geographies.

¹⁰ Weight: 16 to 58 lb bond/88 to 176 gsm.

Return spent imaging supplies through the Xerox[®] Green World Alliance[®] collection/reuse/recycling program. Visit xerox.com/About-Xerox/Recycling

For more information, visit us at xerox.com/Office.

© 2024 Xerox Corporation. All rights reserved. Xerox®, CentreWare®, ConnectKey®, DocuShare®, Global Print Driver®, Green World Alliance®, VersaLink® and WorkCentre® are trademarks of Xerox Corporation in the United States and/or other countries. As an ENERGY STAR® partner, XMPie® is a trademark of XMPie Inc. Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Apple, AirPrint, Bonjour and iBeacon, are trademarks of Apple, Inc., registered in the U.S. and other countries and regions. The Bluetooth® word mark is a registered trademark owned by the Bluetooth SIG, Inc. and any use of such marks by Xerox is under license. Mopria[™] is a registered and/or unregistered trademark of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. Wi-Fi® and Wi-Fi Direct® are registered trademarks of Wi-Fi Alliance®. The information in this brochure is subject to change without notice. 09/24 TSK-5679 BR39214 V6CSS-02UB