

Xerox[®] WorkCentre[™] 5845/5855 Multifunction System

WorkCentre 5800 series multifunction systems are powered by the Xerox® ConnectKey™ Controller. These simple-to-implement systems give you real, practical solutions that easily streamline how you communicate, process and share important information, simplify complex paper-driven tasks and drive down costs while keeping your data secure.



System Specifications	WorkCentre 5845	WorkCentre 5855	
Speed	Up to 45 ppm	Up to 55 ppm	
Monthly Duty Cycle ¹	Up to 175,000 pages	Up to 200,000 pages	
Recommended Average Monthly Print Volume ²	Up to 20,000 pages		
Hard Drive / Processor / Memory	160 GB / 1 GHz Dual-core / 2 GB system		
Connectivity	10/100/1000Base-T Ethernet, High-Speed USB 2.0 direct	print, Optional Wi-Fi (with Xerox® USB Wireless Adapter)	
Controller Features	Unified Address Book, Remote Control Panel, Online Sup	port, Configuration Cloning	
Copy and Print			
First-print-out Time	As fast as 7 seconds		
First-copy-out Time	3.7 seconds from the Platen / 7.6 seconds from the Auton	natic Document Feeder	
Copy and Print Resolution	Up to 600 x 600 dpi input / 4800 x 600 dpi interpolated	d output	
Page Description Languages	Adobe® PostScript® 3™, PDF, PCL® 5c / PCL 6 emulations	, XML Paper Specification (XPS®) (Optional)	
Print Features	Print from USB, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bidirectional Status, Scaling, Job Monitoring, Xerox® PrintBack		
Mobile Printing	Xerox® Mobile Print® (Optional), Xerox® Mobile Print Clou	ud® (Optional)	
Scan			
Standard Features	Scan to Network, Scan to Email, Scan to Folder, Scan to SMB or FTP, Text Searchable PDF, PDF/A, XPS, Linearised PDF, JPEG, TIFF, Scan to USB Memory Device, Single-touch Scanning, TWAIN Support		
Optional Features	ConnectKey for SharePoint®, ConnectKey Share to Cloud, Xerox® Scan to PC Desktop® SE and Professional, numerous solutions available through various Xerox® Alliance Partners		
Fax			
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Enablement (solutions available through various Xerox® Alliance Partners)		
Optional Features	Fax Forward to Email or SMB, Walk-up Fax (one-line and two-line options, includes LAN Fax)		
Security			
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408) (pending), Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions		
Optional Features	McAfee Integrity Control, Xerox® Secure Access, Smart C	Card Kit (CAC/PIV, .NET)	
Accounting			
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax)		
Optional Features	Equitrac Office®, Equitrac Professional®, YSoft® SafeQ®, o various Xerox® Alliance Partners	other network accounting solutions available through	

Device Specifications			
Control Panel Languages	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian, Catalan		
Accessories			
Optional	High Capacity Feeder (HCF) HCF Kit (A4 SEF) (HCF required) HCF Kit (A3 SEF) (HCF required) Envelope Tray (Replaces Tray 2) Basic Office Finisher (optional with 5845 only) Office Finisher Office Finisher with Booklet Maker Hole Punch for Office Finisher High Volume Finisher High Volume Finisher with Booklet Maker Z Fold / C Fold Unit (with High Volume Finisher with Booklet Maker) Post Process Inserter (with High Volume Finisher with Booklet Maker) Convenience Stapler Smart Card Enablement Kit Xerox® Secure Access Unified ID System® (with USB Card Reader) Walk up Fax (One- or Two-line options, includes LAN Fax) ScanFlowStore® Xerox® Unicode International Print Kit Wireless Kit McAfee® Integrity Control Enablement Kit XPS Print Option Kit		
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Access Device, this is an interface to third party access control devices, such as coin machines and card readers. Supports a variety of vending stations available through the Xerox® Alliance Partner Solutions.		
Electrical Requirements			
	Voltage : 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 5 % , 12 A		
Power Consumption	WorkCentre 5845	WorkCentre 5855	
Running (Average)	1,150 watts / hour	1,250 watts / hour	
Standby Mode	290 watts / hour		
Low Power Mode	≤125 watts / hour		
Sleep mode	≤4 watts / hour		
Warm-up	194 seconds		
Low Power Recovery	< 9 seconds		
Operating Environment			
Required Temperature Range	10° to 32° C		
Required Relative	15% to 85%		
Humidity	1370 to 6370		
Humidity Sound Power Levels	Operating 7.1 B(A), Standby: 5.0 B(A)		

Dimensions and Weight	Width	Depth	Height	Weight
Base Configuration with	990 mm	650 mm	1,104 mm	123.3 kg
OCT				
With Basic Office Finisher (5845 only)	1,209 mm	650 mm	1,104 mm	145 kg
With Office Finisher	1,209 mm	650 mm	1,104 mm	149.5 kg
With Office Finisher with Booklet Maker	1,209 mm	650 mm	1,104 mm	165.5 kg
With High Volume Finisher	1,645 mm	650 mm	1,145 mm	192.8 kg
With High Volume Finisher with Booklet Maker, C Fold / Z Fold Unit and Post Process Inserter	1,995 mm	650 mm	1,180 mm	220.3 kg
High Capacity Feeder	389 mm	510 mm	510 mm	30 kg
Certifications				
	FCC Class A Compliant (US), ICES Class A Compliant (Canada) CSA Listed (UL 60950-1, Second Edition) CB Certified (IEC 60950-1, Second Edition) ENERGY STAR® GOST NOM Blue Angel Environmental Choice CE Marked Common Criteria (IEEE 2600.2 standard) (pending) EPEAT GS Mark Citrix® Certified			
Paper Handling				
Single-pass Automatic Doc	ument Feeder			
Capacity ³	200 sheets			
Speed (black and white and colour)	Up to 105 images per minu Up to 200 ipm (duplex)	Up to 105 images per minute (ipm) (simplex) Up to 200 ipm (duplex)		
Paper Sizes Sensed	125 x 138 mm to 297 x 432	2 mm		
Weights	50 gsm to 160 gsm			
Bypass Tray				
Capacity ³	100 sheets			
Sizes	Custom sizes: A6 to A3			
Sizes Weights	Custom sizes: A6 to A3 60 to 216 gsm			
Sizes	Custom sizes: A6 to A3			
Sizes Weights	Custom sizes: A6 to A3 60 to 216 gsm Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies			
Sizes Weights Types	Custom sizes: A6 to A3 60 to 216 gsm Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies			
Sizes Weights Types Trays 1 and 2	Custom sizes: A6 to A3 60 to 216 gsm Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies Tabs	o A3 SEF		

Types	Bond
	Card Stock Glossy
	Hole punched
	Index
	Labels Letterhead
	Lightweight Card Stock
	Plain
	Preprinted
	Recycled Tabs
High Capacity Tandem Tra	L
Capacity ³	Tray 3: 1,600 sheets
	Tray 4: 2,000 sheets
Sizes	Standard Sizes: A4 LEF
Weights	60 to 216 gsm
Types	Bond
	Card Stock Glossy
	Hole punched
	Index
	Letterhead Lightweight Card Stock
	Plain
	Preprinted
	Recycled
High Capacity Feeder (HCF	
Capacity ³	4,000 sheets Optional HCF Kits: 2,000 sheets with A4 HCF Kit or 2,000 sheets with A3 SEF HCF Kit (Optional)
Sizes	A4 LEF Optional HCF Kits: A4 or A3
Weights	60 to 216 gsm
Types	Bond
	Card Stock
	Hole punched Index
	Letterhead
	Plain
	Preprinted Recycled
Envelope Tray (Optional –	Replaces Tray 2)
Capacity ³	Up to 50 envelopes
Sizes	DL, C5
Weights	75 to 90 gsm
Total Capacity	
Device Total Capacity ³	8,700 sheets
Finishing	
Offset Catch Tray (OCT) (O	ptional)
Capacity	Up to 300 sheets of 80 gsm
Basic Office Finisher (Option	
Top Tray Capacity Stacking Tray Capacity	250 sheets of 80 gsm 1,000 sheets of 80 gsm
Top Tray Sizes Stacking Tray Sizes	A6 to A3 A5 to A3
Weights	60 to 216 gsm
Stapling	Single Auto stapling:30 sheets maximum: A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers)
' '	30 sheets maximum: A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)

Office Finisher (Optional)				
Top Tray Capacity Stacking Tray Capacity	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (A4)			
Top Tray Sizes Stacking Tray Sizes	A6 to A3 A5 to A3			
Weights	60 to 216 gsm			
Multiposition Stapling	80 gsm			
Hole Punch (Optional)	2-4 Hole Punch			
Office Finisher with Bookle	t Maker (Optional)			
Top Tray Capacity Stacking Tray Capacity	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (A4)			
Top Tray Sizes Stacking Tray Sizes	A6 to A3 A5 to A3			
Weights	60 to 216 gsm			
Multiposition Stapling	80 gsm			
Hole Punch (Optional)	2-4 Hole Punch			
Booklet Making Capacity ³	40 booklets (2-15 sheets per booklet – 80 gsm or less)			
Booklet Making Sizes	A4 SEF B4 SEF A3 SEF			
Saddle-stitch Stapling	2-15 sheets / 8-60 page booklet 60 to 90 gsm			
Score / Crease	1-15 sheets / unstapled			
High Volume Finisher (HVF) (Optional)			
Capacity ³	Top Tray – 250 sheets Stacking Tray – 3,000 sheets			
Sizes	A6 to A3 / 105 x 148 mm to 297 x 420 mm			
Weights	60 to 216 gsm			
Stapling ³	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch			
Hole Punch (Optional)	2-hole punch 4-hole punch and 4-hole "Swedish" punch			
High Volume Finisher with	Booklet Maker (Optional)			
Capacity ³	Top Tray – 250 sheets Stacking Tray – 3,000 sheets			
Sizes	A6 to A3 / 105 x 148 mm to 297 x 420 mm			
Weights	60 to 216 gsm			
Stapling ³	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch			
Hole Punch (Optional)	2-hole punch 4-hole punch and 4-hole "Swedish" punch			
Booklet Maker Capacity³	Tray stop up: 30 booklets (1-15 sheets per booklet) Tray stop down: Unlimited			
Booklet Maker Sizes	A4 / 210 x 297 mm 216 x 356 mm A3 / 297 x 420 mm			
Booklet Maker Weights	60 to 216 gsm			
Saddle-stitch Stapling ³	Saddle-stitch (2-15 sheets / 8-60 page booklet)			
Folding	V-folding (1-15 sheets / unstapled)			

Z Fold / C Fold Unit (Option	nal with HVF with Booklet Maker)
Capacity ³	50 sheets or unlimited capacity with tray stop in the down position
Sizes	A4 / 210 x 297 mm
Weights	60 to 216 gsm
Post Process Inserter (Option	onal with HVF and HVF with Booklet Maker)
Capacity ³	250 sheets
Sizes	A4 / 210 x 297 mm 216 x 356 mm A3 / 297 x 420 mm
Weights	60 to 216 gsm
Convenience Stapler (Optio	onal)
Capacity ³	50-sheet stapling 5,000 staples Requires a separate outlet
Сору	
First-copy-out Time	3.7 seconds from the Platen / 7.6 seconds from the Single-pass Automatic Document Feeder
Sides (input:output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 9,999
Resolution (max.)	Up to 600 x 600 dpi input / 4800 x 600 dpi interpolated output
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments
Concurrency	Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)
Copy Features	Annotation and Bates™ stamping (with colour capability and font size adjustment) Authentication for Services Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling Transparencies
Xerox® Copier Assistant®	Xerox® Copier Assistant® (XCA) Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more information, visit www.xerox.com

Print	
First-print-out Time	As fast as 7 seconds
Print Resolution	Up to 600 x 600 dpi input / 4800 x 600 dpi interpolated output
Print Features	Application Defaults Banner Sheet Enable / Disable Bidirectional Status Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, High, Enhanced) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Layout / Watermark (N-up (16), Multi-up, Booklet layout / finishing, Fit to new paper size) Overlays Paper Selection by Attribute Print to Fax (requires optional Fax Kit) Sample Set Secure Print Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Store File in Folder Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) TWAIN Print Driver
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT
Operating Systems	Microsoft® Windows® XP (32- and 64-bit) Windows Server 2008 (32- and 64-bit) Windows Vista (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Mac OS 10.5, 10.6, 10.7, 10.8 Solaris® 9, 10 HP-UX® 11v2 IBM® AIX® 5 Redhat® Fedora® Core 15-17 Redhat Enterprise 4 and 5 openSUSE® 11 and 12 Ubuntu® Unix®
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Apple® Bonjour® IPv6 Secure FTP Most protocols not in use can be disabled
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, DHCP Autonet, SSL, NTP, DNS, SSDP
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts
Xerox [®] Mobile Express Driver [®] (X-MED)	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Print Solutions	
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.

Xerox [®] Mobile Print Solution (Optionαl)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction system without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.
Scan	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs(priority is for return of scanned originals and printing concurrent jobs)
Input Speed	Scan at up to 200 ipm colour scanning and black and white – A4 LEF
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)
Maximum Scan Area	A3
Scan Template Management	Support 250 scan templates Create device specific CentreWare scan templates and share via device cloning to other multifunction systems Confirmation sheet options
Network Protocols	FTP, SMB, NetWare, HTTP, HTTPs
File Formats	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and white TIFF (G3MH, G4 MMR compression – single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC)) JPEG XPS Encrypted / Password Protected PDF (for Workflow Scanning) Linearised PDF
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates: • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customised fields viewed on user interface for variable data input
Scan Features	Mixed Size Originals Scan Build Job Compression Quality / File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Driver Bound Originals Edge Erase Reduction / Enlargement
Supported Scan Destinations (Standard)	Scan to Network Server Scan to USB Drive Scan to Email Scan to Client (SMB or FTP) Scan to Mailbox Scan to Secure FTP Scan to Home
Supported Scan Destinations (Optional)	Scan to PC Desktop (Professional and SE) ScanFlowStore Various Xerox® Alliance Partner Solutions
Authentication	Supports Kerberos (UNIX / Windows Server) SMB (Windows Server) NDS LDAP Xerox® Secure Access Unified ID System® Locally on device (internal database) Convenience Authentication (Off-the-shelf USB Card Reader Support), Smart Cards: CAC / PIV and .NET
Scan to Email (Standard)	
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format)
Scan Features	 Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options Scan to Email s/MIME Encryption Email signing (requires Smart Card option) Auto send to self

Network Scanning – Softw	are Solutions
Xerox® Scan to PC Desktop® Professional (Optional)	A desktop offering that provides advanced document imaging, archiving, editing and organisation tools: Nuance PaperPort Professional image viewing and file management software - Complete PDF functionality - Secure PDF workflow of all scanning applications Nuance OmniPage Pro Office (for desktop/client installation) — Professional OCR software for digital archiving and document conversion Image Retriever — provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability
Xerox® ConnectKey™ for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® multifunction system, you can route documents directly into the precise document repository folder, just like you would from your PC. At the multifunction system, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.
Xerox® ConnectKey Share to Cloud (Optional)	ConnectKey Share to Cloud provides organisations with powerful, easy and secure document scanning capabilities that connect your Xerox® multifunction system to popular cloud services and email, such as Google Docs, SalesForce.com, Office 365 and Dropbox and gives employees anytime, anywhere access to their most important documents using mobile devices.
Security	
Features	 Expanded Authentication Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008), NDS, LDAP Xerox® Secure Access Local Authentication (internal database) Smart Card authentication -144k CAC/PIV Card Support (2048 bit certificate key), .NET Secure Data Digitally signed PDF (with Smart Card) Encrypted Scan to Email (with Smart Card) Password Protected PDF (via Workflow scanning; not Scan to Email) Secure Print (up to 10 digit PIN or Network Authentication) Immediate Image Overwrite On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk FIPS 140-2 256 bit Hard Disk Encryption Expanded Authorisation SA access based on network credentials Authorisation per user per service User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver Secure Network Access IP Filter, IPsec, IPv6, SSL, SNMPv3, HTTPs, 802.1X, Cisco® TrustSec integration (optional), Device Security McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, , McAfee Integrity Control Common Criteria Certification (pending)
Xerox® Secure Access Unified ID System® (Optional)	Xerox® Secure Access Unified ID System integrates your Xerox® multifunction systems with your existing employee/student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralised print server. Then, at any multifunction system on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to www.office.xerox.com/software-solutions
Fax	
Network Server Fax Feature	es
Compatibility	ITY (CCITT) group 3 Various Xerox® Alliance Partner Solutions
Maximum Scan Area	A3
Fax Send Features	One- or two-sided scanning (up to A3) Add to send list (50 numbers maximum) Build Job, Speed Dial, Delay send (specific time) Original type (photo, text or photo and text)
Fax Print Features	One- or two-sided printing, staple, Secure Print
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi
Internet Fax Features	
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients

Address Directory Access	Send: Multi-page TIFF, PDF, PDF/A
/	Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white)
Network Protocols	SMTP (send), POP3 (receive)
Compliance	ITU-T T.37 compliant
Walk-up Fax Features (Opti	ional (Customer-installable) – 1 and 2 lines)
Compatibility	ITU (CCITT) Group 3
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analogue terminal adapter utilising T38
Compression / Speed	MH/G3, MMR/SG3
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes
Fax Send Features	LAN Fax (fax from print driver) Auto fax transmission reduction Page-by-page job status at the machine Delay start, Build Job, Favourites Automatic memory resend Automatic cover sheets PSTN Fax Device Address Book (up to 1,000 contacts)
Fax Receive Features	One- or two-sided printing Stapled or unstapled Receive print mode – Manual (size, margin, stock, header) / Auto Output tray selection Up to 200 password protected mailboxes Secure receive Receive timestamp Auto answer delay
Fax Forward	Forward to Email or SMB Location Fax forward on receive only
Fax Reports	Activity, Dial directory, Group directory, Transmission confirmation, Pending fax, Options report, On demand overwrite report, Mailbox report, Broadcast report
Auto Dialing	Speed Dials: 5,000 total (one- or two-line options) Group Dials: Up to 200 groups with up to 400 recipients per group (one- or two-line options) Auto Redial: Up to 14 attempts (per country requirements) • 1 to 25 minute intervals • Batch send (up to memory capacity)
Device Management	
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2
Xerox® CentreWare® Web	 A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher. CentreWare Integration available for Tivoli® NetView®, Unicentre TNG®, Microsoft Management Console (MMC), HP® OpenView®
Novell NDPS/NEPS	Server gateway application: centralised management tool.
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities

Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction systems. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction systems are available to download. www.office.xerox.com/software-solutions
Xerox® SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAPenvironment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at www.office.xerox.com/software-solutions
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions
CentreWare Internet Service	res – Integrated Web Pages Provided by the Device
Device Status	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese
Remote Print Services	
Automatic Meter Reading (AMR) (May not be available in all regions)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Automatic Supplies Replenishment (ASR) (May not be available in all regions)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory (may not be available in all countries).
Accounting	
Xerox® Standard Accountin	g (Standard)
Tracking	Copy, Print, Fax and Scan usage
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 499 Group accounts (Department)
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via a CSV file
Accounting Options – Netw	ork Accounting – Third Party Enablement
	 Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax Numerous solutions are available through Xerox® Alliance Partners. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support WorkCentre requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account Interface with third party accounting terminal for accounting user interface

Supplies	Description	Quantity	Part Number
Toner Cartridge	Includes 2 Toner Cartridges and Waste Toner Bottle	76,000 pages ⁴ (38,000 pages each) ⁴	006R01551
Waste Toner Bottle	Supplied with each Toner Cartridge Box	100,000 pages ⁴	008R12896
Staple Cartridges	Basic Office Finisher – Complete Cartridge – Refill Cartridge	3,000 per cartridge 3,000 per cartridge (9,000 staples)	108R00682 108R00535
	Office Finisher	5,000 per cartridge (15,000 staples)	108R00493
	Office Finisher with Booklet Maker	5,000 per cartridge (15,000 staples)	108R00493
	Office Finisher with Booklet Maker – saddle-stitch stapling	2,000 per cartridge (8,000 staples)	108R01158
	HVF and HVF with Booklet Maker – Complete Cartridge – Refill Cartridge	5,000 per cartridge 5,000 per cartridge (15,000 staples)	008R12912 008R12898
	HVF with Booklet Maker – saddle-stitch stapling	2,000 per cartridge (16,000 staples)	008R12897
	Convenience Stapler – Complete Cartridge – Refill Cartridge	5,000 per cartridge 5,000 per cartridge (15,000 staples)	008R12964 008R12941
Smart Kits®			
Fuser Module	Includes Ozone Filter	400,0004	109R00751
Xerographic Module – Sold		450,000 ⁴	113R00673
Document Handler Feeder Rolls		150,000 feeds	113R00718

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Our products allow use of papers certified by the FSC, PEFC and SFI, and those made with post consumer recycled content and chlorine-free paper. For more information regarding our entire line of paper and specialty media, contact your Xerox® representative or visit us at www.xerox.com/supplies.

Return spent imaging supplies through the Xerox® Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, call 1-800-ASK-XEROX or visit us at www.xerox.com/office



² Expected regular monthly throughput

³ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

⁴ Approximate pages. Declared Yield based on 5 page job size, 6% area coverage, using A4 media. Yield will vary based on media size, image area coverage, media orientation and usage patterns.